

Bullet & Receptacle Insulated Disconnecter

Specifications



Lead section: 0.5~1.5mm²(22~16) Max current: =10A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
MPD1.25-156	0.4	4.0	11.0	2.7	1.7	10.0	21.0	Red

Lead section: 1.5~2.5mm²(16~14) Max current: =15A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
MPD2-156	0.4	4.0	16.0	2.7	1.7	10.0	21.0	Blue
MPD2-195	0.4	5.0	16.0	2.7	1.7	10.0	21.0	

Lead section: 4~6mm²(12~10) Max current: =24A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
MPD5.5-195	0.4	4.0	11.0	4.5	3.4	14.0	25.0	Yellow

Lead section: 0.5~1.5mm²(22~16) Max current: =10A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
FRD1.25-156	0.4	4.0	16.0	2.7	1.7	13.0	24.5	Red

Lead section: 1.5~2.5mm²(16~14) Max current: =15A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
FRD2-156	0.4	4.0	6.3	3.3	2.3	14.0	24.5	Blue
FRD2-195	0.4	5.0	7.0	3.3	2.3	14.0	24.5	

Lead section: 4~6mm²(12~10) Max current: =24A

ITEM.NO.	Thickness (mm)	Dimension (mm)						Color
		b∅	F	D∅	d∅	H	L	
FRD5.5-195	0.4	5.0	7.0	4.5	3.4	14.0	29.5	Yellow

