

DH4-TB 系列日式接线端子



DH4(TB-1503)



DH4(TB-1504)



DH4(TB-1505)




DH4(TB-1506)



DH4(TB-2505)



DH4(TB-2506)



DH4(TB-2510)



DH4(TB-2512)

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:46.5/22/17.5mm
thick/wide/high:46.5/22/17.5mm

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:55.5/22/17.5mm
thick/wide/high:55.5/22/17.5mm

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:63/22/17.5mm
thick/wide/high:63/22/17.5mm

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:73.5/22/17.5mm
thick/wide/high:73.5/22/17.5mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:79/30/19mm
thick/wide/high:79/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:91/30/19mm
thick/wide/high:91/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:140/30/19mm
thick/wide/high:140/30/19mm


导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:163/30/19mm
thick/wide/high:163/30/19mm




DH4(TB-1510)



DH4(TB-1512)



DH4(TB-2503)



DH4(TB-2504)



DH4(TB-3503)



DH4(TB-3504)



DH4(TB-3506)



DH4(TB-3512)

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:103/22/17.5mm
thick/wide/high:103/22/17.5mm

导线截面:0.5-1.5mm ²
wire section:0.5-1.5mm ²
额定电流/电压:15A/600V
rated current/voltage:15A/600V
厚/宽/高:128.5/22/17.5mm
thick/wide/high:128.5/22/17.5mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:55/30/19mm
thick/wide/high:55/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:25A/600V
rated current/voltage:25A/600V
厚/宽/高:67/30/19mm
thick/wide/high:67/30/19mm


导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:35A/600V
rated current/voltage:35A/600V
厚/宽/高:50/30/19mm
thick/wide/high:50/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:35A/600V
rated current/voltage:35A/600V
厚/宽/高:67/30/19mm
thick/wide/high:67/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:35A/600V
rated current/voltage:35A/600V
厚/宽/高:91/30/19mm
thick/wide/high:91/30/19mm

导线截面:0.5-2.5mm ²
wire section:0.5-2.5mm ²
额定电流/电压:35A/600V
rated current/voltage:35A/600V
厚/宽/高:163/30/19mm
thick/wide/high:163/30/19mm

DH4-TB 系列固定式接线端子




DH4(TB-4503)



DH4(TB-4504)



DH4(TB-4505)



DH4(TB-4506)

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:15A/600V

rated current/voltage:15A/600V

厚/宽/高:70/38/23.5mm

thick/wide/high:70/38/23.5mm

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:45A/600V

rated current/voltage:45A/600V

厚/宽/高:85/38/23.5mm

thick/wide/high:85/38/23.5mm

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:45A/600V

rated current/voltage:45A/600V

厚/宽/高:102.5/38/23.5mm

thick/wide/high:102.5/38/23.5mm

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:45A/600V

rated current/voltage:45A/600V

厚/宽/高:120.5/38/23.5mm

thick/wide/high:120.5/38/23.5mm



DH4(TB-4510)



DH4(TB-4512)

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:45A/600V

rated current/voltage:45A/600V

厚/宽/高:222/38/23.5mm

thick/wide/high:222/38/23.5mm

导线截面:0.5-4mm²

wire section:0.5-4mm²

额定电流/电压:45A/600V

rated current/voltage:45A/600V

厚/宽/高:222/38/23.5mm

thick/wide/high:222/38/23.5mm

DH5-TBC 系列固定式大电流接线端子




DH5(TBC-603)(60A3P)



DH5(TBC-604)(60A4P)



DH5(TB G-606)(60A6P)



DH5(TBC-6012)(60A12P)

导线截面:0.5-10mm²

wire section:0.5-10mm²

额定电流/电压:60A/660V

rated current/voltage:60A/660V

厚/宽/高:75.2/36.5/31mm

thick/wide/high:75.2/36.5/31mm

导线截面:0.5-10mm²

wire section:0.5-10mm²

额定电流/电压:60A/660V

rated current/voltage:60A/660V

厚/宽/高:62.6/36.5/31mm

thick/wide/high:62.6/36.5/31mm

导线截面:0.5-10mm²

wire section:0.5-10mm²

额定电流/电压:60A/660V

rated current/voltage:60A/660V

厚/宽/高:128/36.5/31mm

thick/wide/high:128/36.5/31mm

导线截面:0.5-10mm²


wire section:0.5-10mm²

额定电流/电压:60A/660V

rated current/voltage:60A/660V

厚/宽/高:234/36.5/31mm

thick/wide/high:234/36.5/31mm



DH5(TB G-1003)(100A3P)



DH5(TBC-1004)(100A4P)



DH5(TBC-1006)(100A6P)



DH5(TBC-10012)(100A12P)

导线截面:0.5-25mm²

wire section:0.5-25mm²

额定电流/电压:100A/660V

rated current/voltage:100A/660V

厚/宽/高:87/43/37mm

thick/wide/high:87/43/37mm

导线截面:0.5-25mm²

wire section:0.5-25mm²

额定电流/电压:100A/660V

rated current/voltage:100A/660V

厚/宽/高:109/43/37mm

thick/wide/high:109/43/37mm

导线截面:0.5-25mm²

wire section:0.5-25mm²

额定电流/电压:100A/660V

rated current/voltage:100A/660V

厚/宽/高:153/43/37mm

thick/wide/high:153/43/37mm

导线截面:0.5-25mm²

wire section:0.5-25mm²

额定电流/电压:100A/660V

rated current/voltage:100A/660V

厚/宽/高:285/43/35mm

thick/wide/high:285/43/35mm