

Enclosed Type Magnetic starter (Push Button Type)

封闭式起动器 (按钮型)



型号说明 Type designation

UK	Q	22	MB	AC220V
科瑞普 KRIPAL	封闭式启动器 Enclosed type magnetic motor	额定电流 Rated current (AC 440V基准)	分类型 Application	操作电压 Operation voltage
	Q 特殊防护 Special Protection	9 4KW 75 37KW	- 铁壳 Steel case	与接触器一样 Same with the magnetic contactors
	W1 一般防护 General Protection	12 5.5KW 85 45KW	B 铁壳带按钮 Steel case (push button type)	
		18 7.5KW 100 55KW	M 塑料壳 Plastic case	
		22 11KW 125 60KW	MB 塑料壳带按钮 Plastic case(push button type)	
		32 15KW 150 75KW	防护等级 Protection grade	
		40 18.5KW 180 90KW		
		50 22KW 220 132KW		
		65 30KW		

额定容量 Rated capacity

型号 Model	额定容量 Rated capacity (KW)					额定电流 Rated current(A)			AC1类别 AC1 Type
	单相电机 Single-phase motor		三相电机AC3类别 Three-phase motor AC3 Type			三相电机AC3类别 Three-phase motor AC3 Type			
	110V	220V	200V~220V	380V~440V	500V~550V	200V~220V	380V~440V	500V~550V	
UKQ-9MB(UKW1-9MB)	0.4	0.8	2.5	4	4	11	9	7	25
UKQ-12MB(UKW1-12MB)	0.5	1	3.5	5.5	7.5	13	12	12	25
UKQ-18MB(UKW1-18MB)	0.75	1.5	4.5	7.5	7.5	18	18	13	40
UKQ-22MB(UKW1-22MB)	0.9	1.8	5.5	11	15	22	22	22	40
UKQ-32MB	1.2	-	7.5	15	18.5	32	32	28	50
UKQ-40MB	1.7	-	11	18.5	22	40	40	32	60
UKQ-50B	-	-	15	22	30	55	50	43	80
UKQ-65B	-	-	18.5	30	33	65	65	60	100
UKQ-75B	-	-	22	37	37	75	75	64	110
UKQ-85B	-	-	25	45	45	85	85	75	135

外型安装尺寸 External & Mounting dimensions

型号 Model	外形尺寸 External / mounting dimension
UKW1-9MB~22MB	

Enclosed Type Magnetic starter (Push Button Type)

封闭式起动器 (按钮型)

外型安装尺寸 External & Mounting dimensions

型号 Model	外形尺寸 External / mounting dimension		
UKQ-9MB-22MB			
UKQ-32MB-40MB			
UKQ-50B-85B			
触点构成 Contacts form	UKQ-9MB-22MB	UKQ-32MB-40MB	UKQ-50B-85B