

Silencers

Specification

Fluid	Air, Vacuum	
Pressure Range	0~1.0MPa	150PSI
Max Pressure	1.5MPa	250PSI
Temperature Range	0~60°C	32~140°F
Applicable Tube	PU (Polyurethane)	PA(Nylon)

③ Thread Type and Size

55° R(PT,BSPT) Taper Pipe Thread

Code	01	02	03	04	06	08	10	12	16
Thread	R1/8	R1/4	R3/8	R1/2	R3/4	R1	R11/4	R11/2	R2

55° G(BSPP) Thread

Code	G01	G02	G03	G04	G08	G10	G12	G16
Thread	G1/8	G1/4	G3/8	G1/2	G1	G11/4	G11/2	G2

UNF

NPT 60° American Standard Taper Pipe Thread


Code	U10	N01	N02	N02	N04	N06	N08	N10	N12	N16
Thread	10-32UNF	NPT1/8	NPT1/4	NPT3/8	NPT1/2	NPT3/4	NPT1	NPT11/4	NPT11/2	NPT2

Metric Size

Code	M5	M6	M8	M10
Thread	M5x0.8	M6x1	M8x1	M10x1
M12	M12A	M14	M16	M20
M12x1.25	M12Ax1.5	M14x1.5	M16x1.5	M20x1.5

Silencers

BSL



THREAD (R, PT, BSPT)	THREAD (NPT)	THREAD (G, BSPP)
BSL-M5	BSL-U10	BSL-G01
BSL-01	BSL-N01	BSL-G02
BSL-02	BSL-N02	BSL-G03
BSL-03	BSL-N03	BSL-G04
BSL-04	BSL-N04	BSL-G06
BSL-06	BSL-N06	BSL-G08
BSL-08	BSL-N08	BSL-G10
BSL-10	BSL-N10	BSL-G12
BSL-12	BSL-N12	BSL-G16
BSL-16	BSL-N16	